

# Car Charger



e24



Inside

**MASS ONE  
Catalogue**

## General Characteristic

Input Voltage : 12V/24V

Protection: Over Voltage Protection, Over Current Protection, Short Circuit Protection

Temperature: Less than 60°C

Continue working time: Less than 16 hours

EMC: e-mark e24, e8

Efficiency Level: IV

## Model Number Rules

C: Car Charger Series

C: 5W E:10W

xxx: Output Voltage

yyyy: Output Current

m: Color of Enclosure

n: Customer Code (A-Z, 0-9 or Blank, U=USB Output Plug)

Model Number	Input Voltage	Output Voltage	Output Current	Output Power
CCxxxxyyyymn	12V/24V	3.0-5.0V	1.00A Max	5.0W Max
CCxxxxyyyymn	12V/24V	5.1-8.0V	0.98A Max	5.0W Max
CCxxxxyyyymn	12V/24V	8.1-10.0V	0.61A Max	5.0W Max
CExxxxyyyymn	12V/24V	3.0-5.0V	2.00A Max	10.0W Max
CExxxxyyyymn	12V/24V	5.1-8.0V	1.96A Max	10.0W Max
CExxxxyyyymn	12V/24V	8.1-10.0V	1.23A Max	10.0W Max